

## GEOMETRIE E SPECIFICHE

### TR450

Taglie	SMALL	MEDIUM	LARGE
fino a 170.18cm	X		
170.18cm - 182.88cm		X	
182.88cm e oltre			X

GEOMETRIE: 577mm Axle-to-Crown	SMALL	MEDIUM	LARGE
Reach (middle Geo setting)	366.22mm	391.62mm	417.02mm
Stack (middle Geo setting)	580.74mm		
Top Tube (Effective)	568.96mm	594.36mm	619.76mm
Seat Tube (center to top)	420mm		
Head Tube Angle	63°, 63.5°, 64° Adjustable		
ChainStay Length	444.5mm		
Bottom Bracket Height	349.25mm, 355.6mm, 361.95mm Adjustable		
Wheelbase (middle Geo setting)	1155.7mm	1181.1mm	1206.5mm
Head Tube Length	110mm		
Max Rear Tire Clearance	26" x 3.0"		
Rear Hub Spacing	150mm		
Rear Dropout Axle Size	12mm		
Head Tube	Tapered 1.5" Lower / Cane Creek Integrated Top		
BB Shell Width	83mm		

### TR250

Taglie	SMALL	MEDIUM	LARGE
fino a 177.8cm	X		
172.72cm - 187.96cm		X	
182.88cm e oltre			X

GEOMETRIE: 577mm Axle-to-Crown	SMALL	MEDIUM	LARGE
Reach	348.36mm	380.11mm	411.86mm
Stack	596mm		
Top Tube (Effective)	542.98mm	574.73mm	606.48mm
Seat Tube (center to top)	405mm		
Head Tube Angle	64°, 64.5°, 65° Adjustable		
ChainStay Length	429.26mm, 435.61mm, 441.96mm Adjustable		
Bottom Bracket Height	349.25mm, 355.6mm, 361.95mm Adjustable		
Wheelbase	1117.57mm	1149.32mm	1181.10mm
Head Tube Length	110mm		
Max Rear Tire Clearance	26" x 2.8"		
Rear Hub Spacing	150mm		
Rear Dropout Axle Size	12mm		
Head Tube	Tapered 1.5" Lower / Cane Creek Integrated Top		
BB Shell Width	83mm		

## GEOMETRIE E SPECIFICHE

### BLINDSIDE

Taglie	SMALL	MEDIUM	LARGE
fino a 177.8cm	X		
172.72cm - 187.96cm		X	
182.88cm e oltre			X

GEOMETRIE: 578mm Axle-to-Crown	SMALL	MEDIUM	LARGE
Reach	360.53mm	392.28mm	424.03mm
Stack	602.85mm		
Top Tube (Effective)	523.31mm20.6"	555.06mm	586.81mm
Seat Tube (center to top)	431.8mm		
Head Tube Angle	65°		
Seat Tube Angle	73.5°		
ChainStay Length	436.88mm		
Bottom Bracket Height	356mm		
Standover			
Wheelbase	1130.3mm	1162.3mm	1194mm
Head Tube Length	120mm		
Max Rear Tire Clearance	26" x 2.8"		
Rear Hub Spacing	135mm		
Rear Dropout Axle Size	10mm		
Head Tube	(1.5" Lower Cup 49.6mm ID / 1-1/8" Flush Top		
BB Shell Width	73mm		

### BOTTLEROCKET

Taglie	SMALL	MEDIUM	LARGE
fino a 177.8cm	X		
177.8cm - 187.96cm		X	
187.96cm e oltre			X

GEOMETRIE: 540mm Axle-to-Crown	SMALL	MEDIUM	LARGE
Reach	382.8mm	408.2mm	433.6mm
Stack	582.0mm		
Top Tube (Effective)	558.8mm	584.2mm	609.6mm
Seat Tube (center to top)	406mm		
Head Tube Angle	67°		
Seat Tube Angle	72° Actual / 73.5° Artificial		
ChainStay Length	428.9mm		
Bottom Bracket Height	352mm		
Standover	730.77mm		
Wheelbase	1108.2mm	1133.66mm	1159.06mm
Head Tube Length	120mm		
Max Rear Tire Clearance	26" x 2.5"		
Rear Hub Spacing	135mm		
Rear Dropout Axle Size	10mm		
Head Tube	(1.5" Lower Cup 49.6mm ID / 1-1/8" Flush		
BB Shell Width	73mm		

## GEOMETRIE E SPECIFICHE

### COVERT

Taglie	SMALL	MEDIUM	LARGE
fino a 170.18cm	X		
170.18cm - 185.42cm		X	
185.42cm e oltre			X

GEOMETRIE: 545mm Axle-to-Crown	SMALL	MEDIUM	LARGE
Reach	380.43mm	402.83mm	434.18mm
Stack	585.57mm	594.77mm	594.77mm
Top Tube (Effective)	559.46mm	584.67mm	616.02mm
Seat Tube (center to top)	419.1mm	457.2mm	495.3mm
Head Tube Angle	67°		
Seat Tube Angle	73°		
ChainStay Length	433mm		
Bottom Bracket Height	354mm		
Standover	723.5mm	752.5mm	782.9mm
Wheelbase	1112.82mm	1138.86mm	1170.47mm
Head Tube Length	110mm	120mm	120mm
Max Rear Tire Clearance	26" x 2.5"		
Rear Hub Spacing	135mm		
Rear Dropout Axle Size	10mm		
Head Tube	Tapered 1.5" Lower / Cane Creek Integrated Top		
BB Shell Width	73mm		

### TRANS AM

Taglie	SMALL	MEDIUM	LARGE
fino a 170.18cm	X		
172.72cm - 182.88cm		X	
182.88cm e oltre			X

GEOMETRIE: 518mm Axle-to-Crown	SMALL	MEDIUM	LARGE
Reach	377.7mm	400.2mm	422.6mm
Stack	594.4mm	603.7mm	613.0mm
Top Tube (Effective)	565.1mm	590.5mm	615.9mm
Seat Tube (center to top)	419.1mm	457.2mm	495.3mm
Head Tube Angle	68.5°		
Seat Tube Angle	72.5°		
ChainStay Length	423mm + 10mm		
Bottom Bracket Height	319.5mm		
Standover	720mm		
Wheelbase	1069mm42.1"	1095mm43.1"	1121mm
Head Tube Length	110mm4.33"	120mm4.72"	130mm
Max Rear Tire Clearance	26" x 2.5"		
Rear Hub Spacing	135mm		
Rear Dropout Axle Size	10mm or QR		
Head Tube	Campy Integrated 1-1/8		
BB Shell Width	73mm		

## GEOMETRIE E SPECIFICHE

### BANDIT

Taglie	SMALL	MEDIUM	LARGE	X-LARGE
fino a 167.64cm	X			
167.64 - 177.8cm		X		
177.8cm - 187.96cm			X	
187.96cm e oltre				X

GEOMETRIE: 523.9mm Axle-to-Crown (512.9mm Fox 32 140 + 11mm Lower headset cup)	SMALL	MEDIUM	LARGE	X-LARGE
Reach	379.32mm	400.73mm	423.47mm	444.89mm
Stack	581.63mm	595.54mm	604.81mm	618.72mm
Top Tube (Effective)	546.1mm	571.5mm	596.9mm	622.3mm
Seat Tube (center to top)	419.1mm	457.2mm	495.3mm	533.4mm
Head Tube Angle	68°	68°	68°	68°
Seat Tube Angle	74°	74°	74°	74°
ChainStay Length	429.26mm	429.26mm	429.26mm	429.26mm
Bottom Bracket Height	335.28mm	335.28mm	335.28mm	335.28mm
Standover	715.61mm	723.09mm	738.58mm	757.28mm
Wheelbase	1084.58mm	1109.98mm	1135.38mm	1160.78mm
Head Tube Length	110mm	125mm	135mm	150mm
Max Rear Tire Clearance	26" x 2.5"	26" x 2.5"	26" x 2.5"	26" x 2.5"
Rear Hub Spacing	135mm	135mm	135mm	135mm
Rear Dropout Axle Size	10mm	10mm	10mm	10mm
Head Tube	Tapered	Tapered	Tapered	Tapered
BB Shell Width	73mm	73mm	73mm	73mm

### BANDIT 29"

Taglie	MEDIUM	LARGE	X-LARGE
167.64 - 177.8cm	X		
177.8cm - 187.96cm		X	
187.96cm e oltre			X

GEOMETRIE: 555.2mm Axle-to-Crown	MEDIUM	LARGE	X-LARGE
Reach	391.53mm	414.26mm	436.99mm
Stack	627.64mm	636.94mm	646.25mm
Top Tube (Effective)	571.5mm	596.9mm	622.3mm
Seat Tube (center to top)	457.2mm	495.3mm	533.4mm
Head Tube Angle	68.5°	68.5°	68.5°
Seat Tube Angle	74°	74°	74°
Rear Center	445.5mm	445.5mm	445.5mm
ChainStay Length	447.04mm	447.04mm	447.04mm
Bottom Bracket Drop	36.72mm	36.72mm	36.72mm
Wheelbase	1134.64mm	1161.04mm	1187.43mm
Head Tube Length	100mm	110mm	120mm
Max Rear Tire Clearance	29" x 2.4"	29" x 2.4"	29" x 2.4"
Rear Hub Spacing	142mm	142mm	142mm
Rear Dropout Axle Size	12mm	12mm	12mm
Head Tube	Tapered	Tapered	Tapered
BB Shell Width	73mm	73mm	73mm

## GEOMETRIE E SPECIFICHE

### DOUBLE

Taglie	REGULAR	LONG
fino a 182.88cm	X	
182.88cm e oltre		X

GEOMETRIE: 503.4mm Axle-to-Crown	REGULAR	LONG
Reach	391.6mm	417.0mm
Stack	570.12mm	570.12mm
Top Tube (Effective)	565.9mm	591.2mm
Seat Tube (center to top)	355.6mm	355.6mm
Head Tube Angle	68°	
Seat Tube Angle	73°	
ChainStay Length	412.6mm	
Bottom Bracket Height	328mm	
Standover	680.72mm	
Wheelbase	1069.83mm	1095.22mm
Head Tube Length	110mm	
Max Rear Tire Clearance	26" x 2.5"	
Rear Hub Spacing	135mm	
Rear Dropout Axle Size	10mm	
Head Tube	Tapered 49.6mm ID / 44mm ID	
BB Shell Width	73mm	

### BANK

Taglie	SMALL	MEDIUM	LARGE
fino a 172.72cm	X		
167.64cm - 182.88cm		X	
177.8cm e oltre			X

GEOMETRIE: 482mm Axle-to-Crown	SMALL	MEDIUM	LARGE
Reach	379.14mm	404.54mm	429.94mm
Stack	552.93mm		
Top Tube (Effective)	558.8mm	584.2mm	609.6mm
Seat Tube (center to top)	336.5mm		
Head Tube Angle	68.75°		
Seat Tube Angle	72°		
ChainStay Length	406.4mm		
Bottom Bracket Height	320mm		
Standover	655.32mm		
Wheelbase	1033.0mm	1058.4mm	1083.8mm
Head Tube Length	100mm		
Max Rear Tire Clearance	26" x 2.5"		
Rear Hub Spacing	135mm		
Rear Dropout Axle Size	10mm Thru, Nuted or QR		
Head Tube	Tapered 1.5" Lower / Cane Creek Integrated Top		
BB Shell Width	73mm		

## GEOMETRIE E SPECIFICHE

### TOP

Taglie	REGULAR	LONG
fino a 177.8cm	X	
Over 177.8cm		X

GEOMETRIE: 470mm Axle-to-Crown	REGULAR	LONG
Reach	388.0mm	410.4mm
Stack	563.2mm	
Top Tube (Effective)	571.5mm	599.44mm
Seat Tube (center to top)	330.2mm	
Head Tube Angle	69.5°	
Seat Tube Angle	72°	
ChainStay Length	400-419mm	
Bottom Bracket Height	312.4mm	
Standover	635mm	632.4mm
Wheelbase	1028-1049mm	1059-1079mm
Head Tube Length	120mm	
Max Rear Tire Clearance	26" x 2.5"	
Rear Hub Spacing	135mm	
Rear Dropout Axle Size	10mm	
Head Tube	Campy Integrated 1-1/8	
BB Shell Width	73mm	